

AMENDMENTS TO THE CLAIMS:

Claim 1 has been canceled with this amendment.  
Claim 2 has been canceled with this amendment.  
Claim 3 has been canceled with this amendment.  
Claim 4 has been canceled with this amendment.  
Claim 5 has been canceled with this amendment.  
Claim 6 has been canceled with this amendment.  
Claim 7 has been canceled with this amendment.  
Claim 8 has been canceled with this amendment.

9. (currently amended) ~~The method of claim 8, further comprising:~~

A method for comparing a first image to a second image, the method comprising:

deriving a first image data set based on the first image and a second image data set based on the second image, wherein the first and second image data sets include a plurality of data elements and are model representations of the first and second images;

comparing at least one data element in the first image data set with at least one data element in the second image data set, wherein comparing comprises generating a first count of the plurality of data elements in the first image data set that approximately match the plurality of data elements in the second image data set;

re-positioning at least one of the first and second image data sets and the plurality of data elements associated therewith; and  
generating a second count of the plurality of data elements in the first image data set that approximately match the plurality of data elements in the second image data set.

10. (original) The method of claim 9, further comprising:  
repeating the re-positioning step;  
generating a plurality of additional counts of the plurality of data elements in the first image data set that approximately match the plurality of data elements in the second image data, wherein each additional count follows a repetition of the re-positioning step; and  
identifying a maximum comparison point that corresponds to one of the first, second, and plurality of additional counts that approximates a maximum value.
11. (original) The method of claim 10, further comprising:  
predetermining a particular count value, based on a purpose for which the first image is being compared to the second image, that represents a selected level of similarity required for the first and second images to be considered matching; and  
providing a positive match indication when the one of the first, second and plurality of additional counts that corresponds to the maximum comparison

point is equal to or greater than said particular count value.

12. (original) The method of claim 10, further comprising:  
calculating a score that represents a percentage of  
the plurality of data elements in the first image  
data set that approximately match the plurality  
of data elements in the second image data set at  
the maximum comparison point.
13. (original) The method of claim 12, further comprising:  
predetermining a particular score, based on a purpose  
for which the first image is being compared to  
the second image, that represents a selected  
level of similarity required for the first and  
second images to be considered matching; and  
providing a positive match indication when the score  
associated with the maximum comparison point is  
equal to or greater than said particular score.
14. (original) The method of claim 10, further comprising:  
calculating a probability of relationship value that  
represents a relationship of match between the  
plurality of data elements in the first image  
data set and the plurality of data elements in  
the second image data set at the maximum  
comparison point.
15. (original) The method of claim 14, further comprising:  
predetermining a particular probability of  
relationship value, based on a purpose for which  
the first image is being compared to the second

image, that represents a selected level of similarity required for the first and second images to be considered matching: and providing a positive match indication when the probability of relationship value associated with the maximum comparison point is equal to or greater than said particular probability of relationship value.

16. (original) The method of claim 9, wherein re-positioning at least one of the first and second image data sets and the plurality of data elements associated therewith comprises:  
shifting at least one of the first and second image data sets and the plurality of data elements associated therewith.
17. (original) The method of claim 9, wherein re-positioning at least one of the first and second image data sets and the plurality of data elements associated therewith comprises:  
rotating at least one of the first and second image data sets and the plurality of data elements associated therewith.
18. (original) The method of claim 9, wherein re-positioning at least one of the first and second image data sets and the plurality of data elements associated therewith comprises:  
shifting and rotating at least one of the first and second image data sets and the plurality of data elements associated therewith.

19. (original) A method for comparing a first image data set to a second image data set, wherein the first and second image data sets are derived from fingerprint images and include a plurality of data elements comprising at least one of bifurcation representations, rod representations, vector segments associated with bifurcation representations, vector segments associated with rod representations, vector segments not associated with bifurcation representations, vector segments not associated with rod representations, microminutia points, and combinations thereof, the method comprising:

re-positioning at least one of the first and second image data sets, thereby re-positioning the set of data elements associated therewith;  
generating a count of the data elements in the first image data set that approximately match the data elements in the second image data set; and  
repeating said re-positioning and said generating a count until a maximum comparison point is identified, said maximum comparison point being a point at which said count approximates a maximum value.

20. (original) The method of claim 19, further comprising:  
predetermining a particular count value, based on a purpose for which the first image data set is being compared to the second image data set, that represents a selected level of similarity required for the first and second image data sets to be considered matching; and

providing a positive match indication when the count that corresponds to the maximum comparison point is equal to or greater than said particular count value.

21. (original) The method claim 19 further comprising:  
calculating a score that represents a percentage of the data elements in the first image data set that approximately match the data elements in the second image data set at the maximum comparison point.

22. (original) The method of claim 21 further comprising:  
predetermining a particular score, based on a purpose for which the first image data set is being compared to the second image data set, that represents a selected level of similarity required for the first and second image data sets to be considered matching; and  
providing a positive match indication when the score associated with the maximum comparison point is equal to or greater than said particular score.

23. (original) The method of claim 19, further comprising:  
calculating a probability of relationship value that represents a relationship of match between the plurality of data elements in the first image data set and the plurality of data elements in the second image data set at the maximum comparison point.

24. (original) The method of claim 23, further comprising:  
predetermining a particular probability of

relationship value, based on a purpose for which  
the first image is being compared to the second  
image, that represents a selected level of  
similarity required for the first and second  
images to be considered matching: and  
providing a positive match indication when the  
probability of relationship value associated with  
the maximum comparison point is equal to or  
greater than said particular probability of  
relationship value.

25. (original) The method of claim 19, further comprising  
an initial step of:

narrowing the first and second image data sets by  
eliminating those data elements in one of the  
first and second image data sets that do not fit  
within a predetermined qualifying range of  
deviation from data elements in the other of the  
first and second image data sets.

Claim 26 has been canceled with this amendment.

27. (currently amended) ~~The method of claim 26, wherein  
the first and second images are fingerprint images and the  
plurality of data elements are selected from a group  
consisting of:~~

A method for efficiently and accurately comparing a first  
image to a plurality of other images, wherein the first and  
second images are fingerprint images, the method  
comprising:

deriving a first image data set based on the first image and a plurality of other image data sets based on the plurality of other images, wherein each image data set includes a plurality of data elements and is a model representation of a corresponding image, and wherein the plurality of data elements are selected from a group consisting of bifurcation representations, rod representations, vector segments associated with bifurcation representations, vector segments associated with rod representations, vector segments not associated with bifurcation representations, vector segments not associated with rod representations, microminutia points, and combinations thereof; and  
comparing at least one data element in the first image data set with data elements in at least one of the plurality of other image data sets.

Claim 28 has been canceled with this amendment.

Claim 29 has been canceled with this amendment.

30. (currently amended) ~~The method of claim 29, wherein the first and second images are fingerprint images and the plurality of data elements are selected from a group consisting of:~~

A method for efficiently and accurately comparing a first image to a plurality of other images, wherein the first and second images are fingerprint images, the method comprising:



deriving a first image data set based on the first image and a plurality of other image data sets based on the plurality of other images, wherein each image data set includes a plurality of data elements and is a model representation of a corresponding image, and wherein the plurality of data elements are selected from a group consisting of bifurcation representations, rod representations, vector segments associated with bifurcation representations, vector segments associated with rod representations, vector segments not associated with bifurcation representations, vector segments not associated with rod representations, microminutia points, and combinations thereof-;

comparing at least one data element in the first image data set with data elements in at least one of the plurality of other image data sets;

generating a count for each of the plurality of other image data sets, wherein generating the count comprises calculating a quantity of data elements in each of the plurality of other image data sets that approximately match data elements taken from the first image data set;

selecting from the plurality of other image data sets a predetermined number of image data sets having the most data elements that approximately match data elements taken from the first image data set; and

performing a more thorough comparison of the predetermined number of image data sets to the first image data set.

31. (currently amended) ~~The method of claim 26, wherein comparing at least one data element in the first image data set with data elements in at least one of the plurality of other image data sets comprises:~~

A method for efficiently and accurately comparing a first image to a plurality of other images, the method comprising:

deriving a first image data set based on the first image and a plurality of other image data sets based on the plurality of other images, wherein each image data set includes a plurality of data elements and is a model representation of a corresponding image; and

comparing at least one data element in the first image data set with data elements in at least one of the plurality of other image data sets, wherein comparing comprises creating a B-tree data file for each of a plurality of data element types and categorizing and storing, based on a set of data normalization rules, substantially all of the data elements included in the plurality of other image data sets.

32. (original) The method of claim 31, wherein creating a B-tree data file for each of a plurality of data element types and categorizing and storing, based on a set of data normalization rules, substantially all of the data elements included in the plurality of other image data sets, further comprises:

storing each data element in the B-tree data files  
with an identifier that represents association  
with a particular image data set within which the  
data element appears.

33. (original) The method of claim 32, wherein creating a B-tree data file for each of a plurality of data element types and categorizing and storing, based on a set of data normalization rules, substantially all of the data elements included in the plurality of other image data sets, further comprises:

creating a B-tree data file, for each data element type, that reflects substantially all potential relative associations between data elements stored in the data file and the plurality of data element types.

34. (original) The method of claim 32, wherein creating a B-tree data file for each of a plurality of data element types and categorizing and storing, based on a set of data normalization rules, substantially all of the data elements included in the plurality of other image data sets, further comprises:

creating a B-tree data file that reflects  
normalization rules for each data element type,  
including variations of relative position and  
rotation.

35. (original) The method of claim 32, wherein the first and second images are fingerprint images and the plurality of data elements are selected from a group consisting of:

bifurcation representations, rod representations, vector segments associated with bifurcation representations, vector segments associated with rod representations, vector segments not associated with bifurcation representations, vector segments not associated with rod representations, microminutia points, and combinations thereof.

36. (original) The method of claim 32, further comprising:  
comparing at least one target data element from the first image data set to data elements in the B-tree data file having data elements of a same type as each target data element being compared.
37. (original) The method of claim 36, further comprising:  
utilizing the identifiers associated with the data elements listed in the B-tree data files to calculate and note a quantity of data elements in each of the plurality of other image data sets that approximately match data elements taken from the first image data set.
38. (original) The method of claim 37, further comprising:  
selecting from the plurality of other image data sets a predetermined number of image data sets having the most data elements that approximately match the target data elements taken from the first image data set; and  
performing a more thorough comparison of the predetermined number of image data sets to the first image data set.

39. (original) The method of claim 38, wherein the first and second images are fingerprint images and the plurality of data elements are selected from a group consisting of:

bifurcation representations, rod representations, vector segments associated with bifurcation representations, vector segments associated with rod representations, vector segments not associated with bifurcation representations, vector segments not associated with rod representations, microminutia points, and combinations thereof.

40. (currently amended) ~~The method of claim 26, wherein comparing at least one data element in the first image data set with data elements in at least one of the plurality of other image data sets comprises:~~

A method for efficiently and accurately comparing a first image to a plurality of other images, the method comprising:

deriving a first image data set based on the first image and a plurality of other image data sets based on the plurality of other images, wherein each image data set includes a plurality of data elements and is a model representation of a corresponding image; and

comparing at least one data element in the first image data set with data elements in at least one of the plurality of other image data sets, wherein comparing comprises:

creating a directory that progressively lists, based on at least one measured characteristic, a substantial number of a first type of data elements that appear in the plurality of other image data sets, wherein each data element in the directory is listed with an identifier that represents association with a particular image data set within which the data element appears; and comparing data elements of the first type taken from the first image data set to the data elements that are progressively listed in the directory.

41. (original) The method of claim 40, wherein comparing data elements of the first type taken from the first image data set to the data elements that are progressively listed in the directory comprises:  
creating an array having a two-entry cell for each of a range of potential configurations for the first type of data element;  
recording in a first entry of at least one two-entry cell, a quantity value representing a number of consecutive data elements in the directory that demonstrate characteristics that are approximately similar to characteristics of the one of the range of potential configurations for the first type of data element that is associated with the two-entry cell within which the first entry is being recorded; and

recording in a second entry of at least one two-entry cell, an index value corresponding to an initial data element that begins the number of consecutive data elements listed in the directory.

42. (original) The method of claim 41, wherein comparing data elements of the first type taken from the first image data set to data elements that are progressively listed in the directory comprises:

identifying a two-entry cell in the array that is associated with a data element configuration having characteristics approximately identical to a target data element taken from the first image data set; and

comparing the target data element to a group of consecutive data elements listed in the directory, as indicated by the two-entry cell associated with the target data element; and repeating the identifying and comparing steps for at least one additional target data element.

43. (original) The method of claim 42, further comprising generating a count for each of the plurality of other image data sets, wherein generating the count comprises:

utilizing the identifiers associated with the data elements listed in the directory to calculate and note a quantity of data elements in each of the plurality of other image data sets that approximately match data elements taken from the first image data set.

44. (original) The method of claim 43, further comprising:  
selecting from the plurality of other image data sets  
a predetermined number of image data sets having  
the most data elements that approximately match  
data elements taken from the first image data  
set; and

performing a more thorough comparison of the  
predetermined number of image data sets to the  
first image data set.

45. (original) The method of claim 43, further comprising:  
repeating the previous steps substituting at least one  
other type of data elements in place of the first  
type of data elements;

selecting from the plurality of other image data sets  
a predetermined number of image data sets having  
the most data elements that approximately match  
data elements taken from the first image data  
set; and

performing a more thorough comparison of the  
predetermined number of image data sets to the  
first image data set.

46. (original) A method for efficiently and accurately  
comparing a first image data set to a plurality of  
other image data sets, wherein the first and plurality  
of other image data sets are individually derived from  
fingerprint images and include a plurality of data  
elements of a plurality of types, the plurality of  
types comprising at least one of bifurcation  
representations, rod representations, vector segments



associated with bifurcation representations, vector segments associated with rod representations, vector segments not associated with bifurcation representations, vector segments not associated with rod representations, microminutia points, and combinations thereof, the method comprising:

- creating a directory that progressively lists, based on at least one measured characteristic, a substantial number of a first type of data elements that appear in the plurality of other image data sets, wherein each data element in the directory includes an identifier that represents association with a particular image data set within which the data element appears;
- creating an array having a two-entry cell for each of a range of potential configurations for the first type of data element;
- recording in a first entry of at least one two-entry cell, a quantity value representing a number of consecutive data elements in the directory that demonstrate characteristics that are approximately similar to characteristics of the one of the range of potential configurations for the first type of data element that is associated with the two-entry cell within which the first entry is being recorded;
- recording in a second entry of at least one two-entry cell, an index value corresponding to an initial data element that begins the number of consecutive data elements listed in the directory;

identifying a two-entry cell in the array that is associated with a data element configuration having characteristics approximately identical to a target data element of the first type taken from the first image data set; and comparing the target data element to a group of consecutive data elements listed in the directory, as indicated by the two-entry cell associated with the target data element.

47. (original) The method of claim 46, further comprising: repeating the identifying and comparing steps for at least one additional target data element; utilizing the identifiers associated with the data elements listed in the directory to calculate and note a quantity of data elements in each of the plurality of other image data sets that approximately match data elements taken from the first image data set; selecting from the plurality of other image data sets a predetermined number of image data sets having the most data elements that approximately match data elements taken from the first image data set; and performing a more thorough comparison of the predetermined number of image data sets to the first image data set.
48. (original) The method of claim 46, further comprising: repeating the identifying and comparing steps for at least one additional target data element;

utilizing the identifiers associated with the data elements listed in the directory to calculate and note a quantity of data elements in each of the plurality of other image data sets that approximately match data elements taken from the first image data set;

repeating the previous steps substituting at least one other type of data elements in place of the first type of data elements;

selecting from the plurality of other image data sets a predetermined number of image data sets having the most data elements that approximately match data elements taken from the first image data set; and

performing a more thorough comparison of the predetermined number of image data sets to the first image data set.

49. (original) A method for efficiently and accurately comparing a first image data set to a plurality of other image data sets, wherein the first and plurality of other image data sets are individually derived from fingerprint images and include a plurality of data elements of a plurality of types, the plurality of types comprising at least one of bifurcation representations, rod representations, vector segments associated with bifurcation representations, vector segments associated with rod representations, vector segments not associated with bifurcation representations, vector segments not associated with rod representations, microminutia points, and combinations thereof, the method comprising:

creating a B-tree data file for at least one of the plurality of data element types and categorizing and storing, based on a set of data normalization rules, substantially all of the data elements included in the plurality of other image data sets;

storing each data element in the B-tree data files with an identifier that represents association with a particular image data set within which the data element appears; and

comparing at least one target data element from the first image data set to data elements in the B-tree data file having data elements of a same type as each target data element being compared.

50. (original) The method of claim 49, further comprising:  
utilizing the identifiers associated with the data elements listed in the B-tree data files to calculate and note a quantity of data elements in each of the plurality of other image data sets that approximately match data elements taken from the first image data set;  
selecting from the plurality of other image data sets a predetermined number of image data sets having the most data elements that approximately match the target data elements taken from the first image data set; and  
performing a more thorough comparison of the predetermined number of image data sets to the first image data set.